

LITHIUM-POLYMER RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

XPR-5554G

NIGHTSTICK®

Life Depends on Light™



Magnetic Waterproof USB Coupling
Never worry about water getting inside your headlamp.


UP TO 16 HOURS OF RUNTIME IN LOW MODE



Dual-Light Technology, focused spotlight and area floodlight at the same time.



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.



MULTI-POSITION TILT-HEAD DESIGN



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



Includes NS-HMC9 and Stainless Steel Clip Back Plate for zero band application.



160 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

DUAL-FUNCTION HEADLAMP

RECHARGEABLE

ITEM NUMBER/UPC

- XPR-5554G, UPC 0 17398 80788 3

MARKET APPLICATIONS

- Hazardous work environments, industrial, fire & rescue

CERTIFICATIONS

- cULus, CE, ATEX, IECEx

CASE MATERIAL

- Engineered Polymer

SPOTLIGHT LUMENS/RUNTIME

- HIGH: 130L, 7.5 hrs. runtime
- LOW: 70L, 16 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH: 130L, 6.5 hrs. runtime
- LOW: 70L, 12.5 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- 160L, 4.5 hrs. runtime

CANDELA

- HIGH: 1,887

BEAM DISTANCE

- 87m

DUST/WATER RATING

ANSI IP-67 Dustproof / Waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 2.1 in (53 mm)
- WIDTH: 2.6 in (66 mm)
- DEPTH: 1.8 in (46 mm)
- WEIGHT: 3.0 oz (85 g)

BATTERY







- Lithium-Polymer (integrated)

WARRANTY

- Limited lifetime warranty


WHAT'S INCLUDED

- Headlamp
- Lithium-Polymer battery
- Elastic non-slip headband
- Heavy-duty rubber head strap
- Strap Back Plate
- Stainless Steel Clip Back Plate
- NS-HMC9 Mount
- 4' (304 mm) USB Male (Type A) Magnetic Coupler Charge Cord
- Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	130 LUMENS	70 LUMENS	160 LUMENS
	7h 30min	16h	4h 30min
	87m	UP TO 16 HOURS OF RUNTIME IN LOW MODE	
	1887cd		
	2m		
	1m		

Bayco Products, Inc. XPR-5554G
640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
For use with Bayco Li-ion Battery Pack 5554-BATT

 **LISTED**
E 467756
ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE
CE 2575

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV 1 GRPS E-G T135°C
CLASS I ZONE 0 AEx ia IIC T4 Ga
Ⓢ II 1 G Ex ia IIC T4 Ga
Ex ia IIC T4 Ga
UL 20 ATEX 2400
IECEx UL 20.0080
-20°C ≤ Tamb ≤ +40°C
3.7V/Cell 5554-BATT
Um 4.2V

 SEE INSTRUCTION MANUAL
VOIR MANUEL

MFG MM-YY

