

3AA

INTRINSICALLY SAFE INTRANT™ DUAL-LIGHT™ ANGLE LIGHT


XPP-5566-XSERIES



Head rotates 90° - directing beam exactly where it's needed most



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches independently control separate LEDs



Heavy-duty, clip and V-ring securely holds tight to gear in any situation



AVAILABLE IN MULTIPLE COLORS.

200 LUMENS

FL1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	200 LUMENS	100 LUMENS	205 LUMENS
	11h	11h	11h
	401m		
	40256cd		



1-800-233-2155 · 1-469-326-9400 · nightstick.com

**INTRANT®****DUAL-LIGHT™ ANGLE LIGHT****3AA****ITEM NUMBER/UPC**

XPP-5566RX (Red), 0 17398 80629 9  
 XPP-5566GX (Green), 0 17398 80628 2

**MARKET APPLICATIONS**

Hazardous work environments, fire, rescue, industrial and automotive

**CERTIFICATIONS**

- CE, cULus, Atex, IECEx, NFPA

**CASE MATERIAL**

- Glass filled nylon polymer

**LUMENS/RUNTIME****FLASHLIGHT**

- HIGH: 200L, 11 hrs. runtime
- MEDIUM: 110L, 18 hrs. runtime
- LOW: 60L, 33 hrs. runtime
- STROBE

**FLOODLIGHT**

- HIGH: 100L, 11 hrs. runtime
- MEDIUM: 40L, 18 hrs. runtime
- SURVIVAL: 20L, 33 hrs. runtime

**DUAL-LIGHT**

- 205L, 11 hrs. runtime

**CANDELA****FLASHLIGHT**

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

**BEAM DISTANCE****FLASHLIGHT**

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

**WATER RATING**

- IP-67 (dustproof and waterproof)

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- BEZEL DIAMETER: 2.1 in (53mm)
- WEIGHT: 11.1 oz (315g)(with batteries)

**BATTERY**







- 3AA batteries (included)

**WARRANTY**

- Limited Lifetime Warranty

**WHAT'S INCLUDED**

- Angle light
- AA battery carrier
- 3AA batteries
- Instruction manual

FL 1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	<b>200</b> LUMENS	<b>100</b> LUMENS	<b>205</b> LUMENS
	<b>11h</b>	<b>11h</b>	<b>11h</b>
	<b>401m</b>		
	<b>40256cd</b>		
			
			

**Bayco Products, Inc. XPP-5566**  
 640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

For use with Bayco Li-ion Battery Pack 5568-BATT or 5566-CARRIER with 3 AA Energizer Type EN91 or E91 batteries only



E 467756  
 ID 4003544

ELECTRICAL SAFETY  
 INTRINSICALLY SAFE  
 SECURITE INTRINSEQUE

CE 2575

Control Drawing: 5568-CERT-DWG1-03

CLASS I DIV 1 GRPS A-D T4  
 CLASS II & III DIV1 GRPS E-G T135°C  
 CLASS I ZONE 0 AEx ia IIC T4 Ga  
 Ⓢ I M1 Ex ia op is I Ma  
 Ⓢ II 1 G Ex ia op is IIC T4 Ga

Ex ia op is I Ma  
 Ex ia op is IIC T4 Ga  
 DEMKO 17 ATEX 1927  
 IECEx UL 17.0082  
 -20°C ≤ Tamb ≤ +40°C  
 1.5V/Cell Alkaline  
 3.7V/Cell Li-ion  
 IP-67  
 Um: 10V

**CERTIFIED**

**NFPA**

AVAILABLE IN MULTIPLE COLORS.

