






NSR-9920XL

Xtreme Lumens™ Polymer Multi-Function Duty/Personal-Size Dual-Light™ Flashlight w/Magnet - Rechargeable

MARKET APPLICATIONS	Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.
DESCRIPTION	This duty/personal-size rechargeable polymer multi-function Xtreme Lumens™ Dual-Light™ flashlight uses an LED rated at 650 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable beam rated at 304 meters. A 200 lumens unfocused floodlight is integrated in to the housing which is perfect for close-up illumination. Additionally both the flashlight (any brightness mode) and the floodlight can be turned on at the same time for maximum safety and versatility. The flashlight body switch provides momentary or constant-on functionality, a set of user-selectable high, medium or low-brightness settings as well as a disorienting strobe. The second body switch operates the floodlight. The powerful magnet built into the tail-cap provides for hands-free use. The housing is made from glass-filled nylon polymer and has an aircraft-grade 6061-T6 aluminum tail-cap and a 316 stainless steel bezel. Both the tail-cap and the bezel have a Type III hard anodized finish. Power comes from a rechargeable Lithiumion battery. Meets requirements of NFPA-1971-8.6 (2013).
CASE MATERIAL	Glass-filled Nylon Polymer w/ Aircraft-grade 6061-T6 Aluminum Tail Cap & Bezel both with a Type III Hard Anodized Finish - Red
DIMENSIONS	Length: 9.5 inches (241 mm) • Handle diameter: 1.2 inches (30 mm) • Head diameter: 1.6 inches (41 mm)
WEIGHT	Weight: 9.9 oz. (241 g) with battery installed.
LENS	Unbreakable polycarbonate with scratch resistant coating.
LIGHT SOURCE	LED
LIGHT OUTPUT	Flashlight: High - 650 lumens, Medium - 300 lumens, Low - 150 lumens, Strobe - 300 lumens • Floodlight: 200 lumens • Dual-Light: 400 lumens
ON/OFF	First Body Switch & Tail Switch - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe • Second Body Switch - Floodlight • First (or Tail Switch) & Second Body Switch - Dual-Light
RUN-TIME	Flashlight: High - 4.25 hrs, Medium - 9.5 hrs, Low - 18.75 hrs, Strobe - 6 hrs • Floodlight: 7.25 hrs • Dual-Light: 7 hrs
BATTERY	2-cell, 6 Volt Lithium-ion battery pack
CHARGING	Charger is wall or vehicle mountable. Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.
FEATURES	<ul style="list-style-type: none"> • LED technology • Flashlight/Floodlight/Dual-Light™ • Momentary or constant-on plus 3 brightness levels & strobe • Sharp focused flashlight beam • High-efficiency deep parabolic reflector • Effective beam distance of 304 meters (over 990 feet) • Unfocused wide-beam floodlight for close-up illumination • Dual-Light (flashlight & floodlight at the same time) for maximum safety & versatility • Glass-filled nylon polymer housing • Aircraft-grade 6061-T6 aluminum tail cap and bezel both with Type III hard anodized finish • Non-slip grip • Flashlight/strobe – body & tail switch (tandem operation) • Floodlight – second body switch • Waterproof • Impact & chemical resistant • Meets requirements of NFPA-1971-8.6 (2013) • Serialized for personal identification • Powered by Lithium-ion rechargeable battery (included)

FL1 STANDARD	HIGH	MEDIUM	LOW
	650 LUMENS	300 LUMENS	100 LUMENS
	4.25h	9.5h	18h
	304m	212m	115m
	23142cd	11302cd	6028cd
	2m / 1m		

WARRANTY Limited Lifetime Warranty

APPROVALS



OPTIONAL ACCESSORIES 5 Bank Charger, Direct Wire Kit, USB Charging Cable, Red, Yellow & Blue Safety Cones

Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

Bayco Products, Inc. • 640 South Sanden Blvd. • Wylie, TX 75098 • 1-800-233-2155 • 1-469-326-9400 • www.nightstick.com

PDS-NSR-9920XL-19