PRODUCT FACT SHEET

ProTac HL®3
HIGH LUMEN LITHIUM TACTICAL FLASHLIGHT

MARKET APPLICATIONS: Law Enforcement, Security, Emergency Medical Services, Sporting Goods, Hardware/Tool, Consumer

DESCRIPTION: With 1,100 lumens of blinding light, the ProTac HL®3 is the newest and brightest addition to the ProTac® series. The ProTac HL®3 offers the latest in power LED technology and three different user selectable programs. The combination of size and output from the C4® LED result in one of the brightest tactical lights for its' size. Packaged with a removable pocket clip, holster and sure grip rubber sleeve.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS: Length: 7.10 in. (18.03 cm) Barrel Diameter: 1.0 in. (2.54 cm)
Head Diameter: 1.64 in. (4.17 cm) Tri-Lobe Diameter: 1.73 in. (4.39 cm)

WEIGHT: 9.3 oz (263 grams) with batteries

LENS: Glass lens with anti-reflective coating, gasket sealed.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Optimized electronics provides thermal management and regulated intensity.



ON/OFF: Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/high.

RUN TIME: See chart. All claims to 10% of initial lumen output. Strobe: 2 continuous hours.

BATTERY: Three (3) 3 Volt CR123A Lithium batteries. CR123A batteries have a shelf life of 10 years.

FEATURES:



C4® LED technology for extreme brightness.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
1 meter impact resistance tested.
LED Solid State Power Regulation provides maximum light output throughout battery life.
TEN-TAP® programmable switch allows user to select one of three different programs.
Anti-roll facecap.
Removable pocket clip.
Sure grip rubber sleeve.
Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS: Meets applicable European Community directives. CE

OPTIONAL ACCESSORIES: N/A

	FL1 STANDARD	HIGH	LOW
OUTPUT		1,100 LUMENS	35 LUMENS
RUNTIME		2h	43h
DISTANCE		379m	69m
INTENSITY		36,000cd	1,200cd

Strobe Runtime: 2 hours

All performance claims tested to ANSI/NEMA FL1-2009 Standard
Issued: 10/29/2013
Revised: 07/27/2015 **Rev:** 3 Made In China **Document #223**