


TLR-8® G sub**COMPACT RAIL-MOUNTED TACTICAL LIGHT WITH GREEN LASER
SIG SAUER® P365® // SIG SAUER® P365® XL**

DESCRIPTION:	Ultra-lightweight & compact, the TLR-8® G sub is a weapon-mounted tactical light with an integrated green laser. This light features the latest in LED technology for high-lumen operation and provides 1.5 hours of continuous run time from a single lithium battery. The specialized clamp system allows for mounting on SIG SAUER® P365® and P365® XL accessory rails.
CASE MATERIAL:	Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish Switch housing: Impact- and chemical-resistant engineered polymer
DIMENSIONS:	Width: 1.16 in (2.95 cm) Height: 1.63 in (4.14 cm) Length: 2.51 in (6.38 cm)
WEIGHT:	2.77 oz (78.53 grams) with battery (included with purchase)
LENS:	High temperature, shock-mounted, impact-resistant BOROFLOAT® glass
LIGHT SOURCE:	LED: White, impervious to shock with a 50,000-hour lifetime Laser: 510-530nm green laser
LIGHT OUTPUT:	500 lumens, 5,000 candela peak beam intensity and 141 m beam distance Custom TIR optic produces a concentrated beam with optimum peripheral illumination. Optimized electronics provide regulated intensity. Laser provides long-range targeting.
ON/OFF:	Customizable rear switches left and right of trigger guard provide ambidextrous operation. Quick press for constant on operation and press and hold for momentary operation. Double tap either switch within ¼ second to activate strobe (if enabled).
RUN TIME:	LED: 1.5 continuous hours to the 10% output level LED and laser combined: 1.5 continuous hours to the 10% output level Laser only: 11 hours regulated output
BATTERY:	One (1) 3-volt CR123A lithium battery with a storage life of 10 years
FEATURES:	Ultra-lightweight and compact High-power LED for extreme brightness Ambidextrous operation One handed snap-on and tighten interface keeps hands away from muzzle when attaching or detaching Securely fits on P365® rail systems using the provided key and jaw set Extensively live fire tested Operating temperature: -40°F to +120°F IPX4-rated design; water-resistant operation Serialized for positive identification
APPROVALS:	 Meets applicable European Community Directives
WARRANTY:	Streamlight's Limited Lifetime Warranty
OPTIONAL ACCESSORIES:	Mounting adapters

All Rights Reserved. SIG SAUER® and P365® are registered trademarks of SIG SAUER, Inc. Streamlight has not sought endorsement of this product from SIG SAUER, Inc.

BOROFLOAT® is a registered trademark of SCHOTT AG.

EXPORT CONTROLS: The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations ("EAR"). The exported sale, transfer or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor.